

# Options Suffix Information



When specifying options on Paramount products, add hyphens between options

ELECTRICAL	
SUFFIX	DESCRIPTION
<b>BALLASTS</b>	
D4	< 10% THD (Consult Factory)
D7	DC Volt Ballast
D8	Low temp Magnetic (N/A T8)
D9	Magnetic (Consult Factory) (N/A 40/50 BX)
E0	Low Temp Electronic (N/A T12 RS & VHO)
E2	2 Electronic Ballasts
E3	3 Electronic Ballasts
E4	4 Electronic Ballasts
E8	High Light Output 32W T8 Ballast
E9	Rapid Start Electronic Ballast
<b>EMERGENCY</b>	
B0	Bodine LP500
B1	Bodine BDL700 WET
B2	Bodine BDL500 WET
B3	Bodine BDL900 WET
B4	Bodine B70A DRY / IOTA I-48
B5	Bodine B50 DRY / IOTA I-80
B6	Bodine B30 DRY
B7	Bodine LP550 DRY
B9	Bodine BHD65U Hazardous Location
I1	IOTA I-48 DL WET
I2	IOTA I-320 DL WET
I3	IOTA I-40 DL WET
I4	IOTA I-48 DRY
I5	IOTA I-320 DRY
I8	IOTA ISL-28 DRY
I9	IOTA ISL-54 DRY
<b>DIMMING</b>	
D1	Lutron Eco10 Dimming
D2	Electronic Dimming
<b>WIRING</b>	
W1	Cord & Plug (Specify, N/A Haz. Loc.)
W2	Quick Disconnect
W3	Remote Ballast Box (N/A Haz. Loc.)
W4	Inboard/Outboard Wiring (Dual Switching)
W5	Rear Wire Entry
W6	Ballast Disconnect
<b>FUSING &amp; SWITCHING</b>	
F1	GLR/HLR Fusing (Fast)
F2	GMF/HLR Fusing (Slow)
F3	HPS/FEE Fusing (External, N/A Haz. Loc.)
F9	Switch (Specify, N/A Haz. Loc.)
<b>MISC ELECTRICAL</b>	
Y1	Night Light (Consult Factory)
Y3	Quartz Restrike (N/A Haz. Loc.)
Y4	Quartz Mini Can Socket (Replacement Only)
Y5	RFI Suppressors/Filters
Y6	Flex-Loc® Lamp Holder (Med Bi-Pin Only: T8, T12)
L1	Medium Base Lampholder (100W-150W)

LENSING	
SUFFIX	DESCRIPTION
<b>LENSES AND ACCESSORIES</b>	
C0	Red Acrylic Lens
C1	Blue Acrylic Lens
C2	Green Acrylic Lens
C3	Amber Acrylic Lens
C9	Frosted Acrylic Lens
H0	Special Lens (Specify)
H1	Tandem Lens With Joiner Band
H2	.150 Extra Heavy Clear Acrylic
H3	.150 Extra Heavy White Acrylic
H5	.156 C73 Tempered Glass
H6	.187 Clear Tempered Glass
H7	2x2 HID Acrylic Drop Lens (Specify)
J0	Lamp Sleeve (Specify Type & Color)
J2	.060 Clear Acrylic Overlay
J3	.187 Prismatic Polycarbonate (P12)
J4	.020 White Acrylic Overlay (Lamp Side)
J5	.250 Clear Polycarbonate
J6	.080 Clear Polycarbonate Overlay
J7	Louver (Specify)
J8	Wire Guard
J9	RFI Lens (Specify Pattern)
K0	.200 V825 Acrylic
K2	.140 KSH-12 Acri-Tuf Acrylic
K3	.187 KSH-12 Acri-Tuf Acrylic
K4	Odd Size Acrylic Drop Lens
K5	Odd Size Polycarbonate Drop Lens
K6	External Prisms
K7	.140 Prismatic Acrylic (P12) (Craft Lite)
K8	Reflector Tape (Consult Factory)

CONSTRUCTION	
SUFFIX	DESCRIPTION
<b>FASTENERS</b>	
T1	Stainless Steel Latches
T2	Stainless Steel Screws
T3	Tamper Resistant (Hex Screw w/pinSTD, Others Avail.)
T4	Polycarbonate Latches (Tuff Lite)
T5	Celcon Latches (Marine Tuff Lite)
*T6	Screw-on End Caps (Craft Lite® Only)
<b>GASKETING</b>	
V1	External Gasketing
V3	No Silicone Sealant Used
<b>BODY &amp; LENS FRAME</b>	
G9	Flange with 6" Deep Ceiling Mounting
P11	Guardcraft® Antimicrobial Coating
P9	Special Paint Color (Specify, Chip Required)
S1	Special Material (Specify)
S2	Stainless Steel Housing
S3	Stainless Steel Exterior
S4	Complete Stainless Steel
S5	Stainless Steel Lens Frame
S6	Stainless Steel Lens Frame/Trim Frame
W0	Weep Holes
X3	Continuous-welded Seams
X4	Plenum Access Panel
X5	Special Cord Quick Disconnect
X6	3/4" Flange or Hub Wire Entry
X7	3/4" Knock Out Wire Entry
X8	3/4" Hole Wire Entry
X9	Receptacle
Z0	Aluminized Steel Mounting Flange (Booth Lite)
<b>REFLECTORS</b>	
R0	Asymmetric Reflector
R1	Reflector End Caps (CMC)
R2	V Reflector (CMC) 4FT
R3	No Uplight Reflector (CMC)
R4	Asymmetric Reflector (Specify)
R5	Specular Aluminum Reflector
R6	Internal Reflector
R7	Stainless Steel Reflector
R8	Pre-Painted Aluminum Reflector
R9	Adjustable Specular Aluminum Reflector

MOUNTING SYSTEMS	
SUFFIX	DESCRIPTION
<b>MOUNTING</b>	
M0	Marine Mounting Straps
M1	Pendant Mounting Means (Pendants By Others)
M2	Mounting Bracket Kit (Surface/Chain)
M3	In-Row (Row Information Required)
M4	Ice Tong Hangers (CMC)
M5	Aligner Kits (CMC)
M6	Angle Mounting Brackets (Consult Factory)
M7	Stainless Steel Hanger Strap
M8	Mounting Yoke
M9	Wall Mounting
<b>PLASTER FRAMES</b>	
P1	Zinc Coated Plaster Frame
P3	Stainless Steel Plaster Frame
<b>CEILING SYSTEMS</b>	
G1	1.5" T-Bar
G2	2" T-Bar
G4	1" & 1.5" T-Bar With Flush Lens
G5	2" T-Bar With Flush Lens
G0	1.5" T-Bar Special

**\*NOTE: T6 OPTION IN CRAFT LITES REQUIRE W5 OPTION ALSO**

Use this glossary as a reference on options.

Please note that these suffixes are not available on all models.